

Environmental Protection Agency

§ 98.75

§ 98.74 Monitoring and QA/QC requirements.

(a) You must continuously measure the quantity of gaseous or liquid feedstock consumed using a flow meter. The quantity of solid feedstock consumed can be obtained from company records and aggregated on a monthly basis.

(b) You must document the procedures used to ensure the accuracy of the estimates of feedstock consumption.

(c) You must determine monthly carbon contents and the average molecular weight of each feedstock consumed from reports from your supplier. As an alternative to using supplier information on carbon contents, you can also collect a sample of each feedstock on a monthly basis and analyze the carbon content and molecular weight of the fuel using any of the following methods listed in paragraphs (c)(1) through (c)(8) of this section, as applicable.

(1) ASTM D1945-03 Standard Test Method for Analysis of Natural Gas by Gas Chromatography (incorporated by reference, *see* § 98.7).

(2) ASTM D1946-90 (Reapproved 2006) Standard Practice for Analysis of Reformed Gas by Gas Chromatography (incorporated by reference, *see* § 98.7).

(3) ASTM D2502-04 (Reapproved 2002) Standard Test Method for Estimation of Mean Relative Molecular Mass of Petroleum Oils from Viscosity Measurements (incorporated by reference, *see* § 98.7).

(4) ASTM D2503-92 (Reapproved 2007) Standard Test Method for Relative Molecular Mass (Molecular Weight) of Hydrocarbons by Thermoelectric Measurement of Vapor Pressure (incorporated by reference, *see* § 98.7).

(5) ASTM D3238-95 (Reapproved 2005) Standard Test Method for Calculation of Carbon Distribution and Structural Group Analysis of Petroleum Oils by the n-d-M Method (incorporated by reference, *see* § 98.7).

(6) ASTM D5291-02 (Reapproved 2007) Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants (incorporated by reference, *see* § 98.7).

(7) ASTM D3176-89 (Reapproved 2002) Standard Practice for Ultimate Analysis of Coal and Coke (incorporated by reference, *see* § 98.7).

(8) ASTM D5373-08 Standard Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal (incorporated by reference, *see* § 98.7).

(d) Calibrate all oil and gas flow meters (except for gas billing meters) and perform oil tank measurements according to the monitoring and QA/QC requirements for the Tier 3 methodology in § 98.34(b).

(e) For quality assurance and quality control of the supplier data, on an annual basis, you must measure the carbon contents of a representative sample of the feedstocks consumed using the appropriate ASTM Method as listed in paragraphs (c)(1) through (c)(8) of this section.

(f) Facilities must continuously measure the quantity of waste gas recycled using a flow meter, as applicable. You must determine the carbon content and the molecular weight of the waste recycle stream by collecting a sample of each waste recycle stream on a monthly basis and analyzing the carbon content using the appropriate ASTM Method as listed in paragraphs (c)(1) through (c)(8) of this section.

(g) If CO₂ from ammonia production is used to produce urea at the same facility, you must determine the quantity of urea produced using methods or plant instruments used for accounting purposes (such as sales records). You must document the procedures used to ensure the accuracy of the estimates of urea produced.

§ 98.75 Procedures for estimating missing data.

A complete record of all measured parameters used in the GHG emissions calculations is required. Therefore, whenever the monitoring and quality assurance procedures in § 98.74 cannot be followed (e.g., if a meter malfunctions during unit operation), a substitute data value for the missing parameter shall be used in the calculations following paragraphs (a) and (b) of this section. You must document and keep records of the procedures used for all such estimates.

§ 98.76

40 CFR Ch. I (7–1–10 Edition)

(a) For missing data on monthly carbon contents of feedstock or the waste recycle stream, the substitute data value shall be the arithmetic average of the quality-assured values of that carbon content in the month preceding and the month immediately following the missing data incident. If no quality-assured data are available prior to the missing data incident, the substitute data value shall be the first quality-assured value for carbon content obtained in the month after the missing data period.

(b) For missing feedstock supply rates or waste recycle stream used to determine monthly feedstock consumption or monthly waste recycle stream quantity, you must determine the best available estimate(s) of the parameter(s), based on all available process data.

§ 98.76 Data reporting requirements.

In addition to the information required by § 98.3(c), each annual report must contain the information specified in paragraphs (a) and (b) of this section, as applicable for each ammonia manufacturing process unit.

(a) If a CEMS is used to measure CO₂ emissions, then you must report the relevant information required under § 98.37(e)(2)(vi) for the Tier 4 Calculation Methodology and the following information in this paragraph (a):

(1) Annual quantity of each type of feedstock consumed for ammonia manufacturing (scf of feedstock or gallons of feedstock or kg of feedstock).

(2) Method used for determining quantity of feedstock used.

(b) If a CEMS is not used to measure emissions, then you must report the following information:

(1) Annual CO₂ process emissions (metric tons) for each ammonia manufacturing process unit.

(2) Monthly quantity of each type of feedstock consumed for ammonia manufacturing for each ammonia processing unit (scf of feedstock or gallons of feedstock or kg of feedstock).

(3) Method used for determining quantity of monthly feedstock used.

(4) Whether carbon content for each feedstock for month n is based on reports from the supplier or analysis of carbon content.

(5) If carbon content of feedstock for month n is based on analysis, the test method used.

(6) Sampling analysis results of carbon content of petroleum coke as determined for QA/QC of supplier data under § 98.74(e).

(7) If a facility uses gaseous feedstock, the carbon content of the gaseous feedstock, for month n, (kg C per kg of feedstock).

(8) If a facility uses gaseous feedstock, the molecular weight of the gaseous feedstock (kg/kg-mole).

(9) If a facility uses gaseous feedstock, the molar volume conversion factor of the gaseous feedstock (scf per kg-mole).

(10) If a facility uses liquid feedstock, the carbon content of the liquid feedstock, for month n, (kg C per gallon of feedstock).

(11) If a facility uses solid feedstock, the carbon content of the solid feedstock, for month n, (kg C per kg of feedstock).

(12) Annual CO₂ emissions associated with the waste recycle stream for each ammonia process unit (metric tons)

(13) Carbon content of the waste recycle stream for month n for each ammonia process unit (kg C per kg of waste recycle stream).

(14) Volume of the waste recycle stream for month n for each ammonia process unit (scf)

(15) Method used for analyzing carbon content of waste recycle stream.

(16) Annual urea production (metric tons) and method used to determine urea production.

(17) Uses of urea produced, if known, such as but not limited to fertilizer, animal feed, manufacturing of plastics or resins, and pollution control technologies.

(c) Total pounds of synthetic fertilizer produced through and total nitrogen contained in that fertilizer.

§ 98.77 Records that must be retained.

In addition to the records required by § 98.3(g), you must retain the following records specified in paragraphs (a) and (b) of this section for each ammonia manufacturing unit.